

# Best Available Copy

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets

(11)

Veröffentlichungsnummer:

(11)

Publication number:

(11)

Numéro de publication:

0 748 460

Internationale Anmeldung veröffentlicht durch die  
Weltorganisation für geistiges Eigentum unter der Nummer:

**WO 95/23987** (art.158 des EPf).

International application published by the World  
Intellectual Property Organisation under number:

**WO 95/23987** (art.158 of the EPC).

Demande internationale publiée par l'Organisation  
Mondiale de la Propriété sous le numéro:

**WO 95/23987** (art.158 de la CBE).

THIS PAGE BLANK (USPTO)



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> :

G02B 6/00, 6/44

A1

(11) International Publication Number:

WO 95/23987

(43) International Publication Date:

8 September 1995 (08.09.95)

(21) International Application Number: PCT/GB95/00449

(22) International Filing Date: 2 March 1995 (02.03.95)

(30) Priority Data:

94301511.5 2 March 1994 (02.03.94)

EP

(34) Countries for which the regional or  
international application was filed:

GB et al.

(71) Applicant (for all designated States except US): BRITISH  
TELECOMMUNICATIONS PUBLIC LIMITED COM-  
PANY [GB/GB]; 81 Newgate Street, London, EC1A 7AJ  
(GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): FROST, Peter, Lewis,  
John [GB/GB]; 14 Copswood Close, Kesgrave, Ipswich,  
Suffolk IP5 7QF (GB). JESSOP, Paul, David [GB/GB];  
5 Waypond Court, Wellesley Road, Clacton-on-Sea, Essex  
CO15 3PW (GB).(74) Agent: PRATT, David, Martin; BT Group Legal Services,  
Intellectual Property Dept., 13th floor, 151 Gower Street,  
London WC1E 6BA (GB).(81) Designated States: AU, CA, CN, JP, KR, NZ, SG, US.  
European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR,  
IE, IT, LU, MC, NL, PT, SE).


Published

With international search report.

(54) Title: OPTICAL FIBRE CUSTOMER LEAD IN

## (57) Abstract

A customer lead in unit (C) guides an optical fibre transmission line through an aperture (7) in the wall (8a, 8b) of a customer's premises. The unit (C) comprises a hollow wall plug (1) which is frictionally engageable within the aperture (7), and a pair of complementary bend control pieces (2), each having a bend control surface (2a) formed with a curved bend control groove (4) whose curvature conforms with minimum bend radius requirements for the optical fibre transmission line. The bend control pieces (2) are formed with engagement portions (3) which inter-engage with a complementary engagement portion (1a) formed at one end of the wall plug (1) to grip the wall plug between the two bend control pieces. The bend control grooves (4) are positioned so as to define a bend control channel that is contiguous with the hollow interior of the wall plug (1) when the wall plug is gripped by the two bend control pieces (2).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

OPTICAL FIBRE CUSTOMER LEAD IN

This invention relates to optical fibre customer lead in (CLI), that is to say to the way in which optical fibres (such as telecommunications optical fibres) are led into  
5 customers' premises.

In the United Kingdom, the telecommunications network includes a trunk network which is substantially completely constituted by optical fibre, and a local access network which is substantially completely constituted by copper  
10 pairs. Eventually, it is expected that the entire network, including the access network, will be constituted by fibre.

The ultimate goal is a fixed, resilient, transparent telecommunications infrastructure for the optical access network, with capacity for all foreseeable service  
15 requirements. One way of achieving this would be to create a fully-managed fibre network in the form of a thin, widespread overlay for the whole access topography, as this would exploit the existing valuable access network infrastructure. Such a network could be equipped as needs  
20 arise, and thereby could result in capital expenditure savings, since the major part of the investment will be the provision of terminal equipment on a 'just in time' basis. It should also enable the rapid provision of extra lines to new or existing customers, and flexible provision or  
25 reconfiguration of telephony services.

In order to be completely future proof, the network should be single mode optical fibre, with no bandwidth limiting active electronics within the infrastructure. Consequently, only passive optical networks (PONs) which can  
30 offer this total transparency and complete freedom for upgrade, should be considered.

In a PON, a single optical fibre is fed out from the exchange head-end (HE), this fibre being fanned out via passive optical splitters at cabinets and distribution points  
35 (DPs) to feed optical network units (ONUs). The ONUs can be in customers' premises, or in the street serving a number of

- 2 -

customers. The use of optical splitters enables sharing of feeder fibre and exchange based optical line termination (OLT) equipment, thereby giving PONs a cost advantage. In the United Kingdom, simplex PONs are planned, so that each  
5 customer is serviced by a pair of optical fibres.

In order to achieve the goal of providing a fixed, resilient, transparent telecommunications optical fibre access network, it will be important to minimise the installation costs at each part of the network. The present  
10 invention is concerned with minimising the cost of installation of fibre from a customer's premises to the nearest network node, and in particular to a cost-effective way of getting fibre into a customer's premises. In this connection, it should be noted that the preferred way of  
15 installing fibre is by the well known fibre blowing process (see EP 108590). In this process, a fibre unit (usually a two-fibre unit for residential premises) is blown through a small diameter (5mm) polyethylene tube.

The main problem to be overcome in feeding such a tube  
20 into a customer's premises arises from the fact that the tube must be fed along the outer wall of the premises and then turned through 90°, so as to pass through a hole formed in the wall. It must then be turned through 90° so that it can be fed along the inner wall of the premises. In each case, the  
25 turning must be accomplished without giving rise to optical loss in the blown-in fibre when it is live.

A known CLI apparatus is constituted by a pair of CLI units, one for fixing to the external surface of a customer's premises wall and one for fixing to the internal surface of  
30 that wall. Each of these units is fairly large, as it accommodates a complete loop of tube (fibre), the loop having a radius greater than the minimum bend radius (100mm) for this type of tube. The hole drilled through the wall between the two CLI units has a fairly large diameter so as to  
35 accommodate a bend limiting conduit through which the tube (fibre) passes between the two units. Not only are these CLI units relatively large and require the drilling of a

- 3 -

relatively large diameter hole, but they are also expensive and time-consuming to fit. Presently, they are used for business premises CLI, where their cost can be justified by the number of lines normally installed for such premises.

- 5 For residential customers, however, which usually have only one line, these units are far too expensive. In this connection, it should be noted that there are 14 million residential premises in the United Kingdom.

The present invention provides a customer lead in unit  
10 for guiding an optical fibre transmission line through an aperture in the wall of a customer's premises, the unit comprising a hollow wall plug which is frictionally engageable within said aperture, and a pair of complementary bend control pieces, each bend control piece having a bend  
15 control surface formed with a curved bend control groove whose curvature conforms with minimum bend radius requirements for the optical fibre transmission line, the bend control pieces being formed with engagement portions which inter-engage with a complementary engagement portion  
20 formed at one end of the wall plug to grip the wall plug between the two bend control pieces, and the bend control grooves being positioned so as to define a bend control channel that is contiguous with the hollow interior of the wall plug when the wall plug is gripped by the two bend  
25 control pieces.

Conveniently, a flange formed at said one end of the wall plug constitutes the complementary engagement portion, and each of the bend control pieces is formed with a complementary groove formed in its bend control surface, said  
30 grooves constituting the engagement portions.

The invention further provides customer lead in apparatus for guiding an optical fibre transmission line through an aperture in the wall of a customer's premises, the apparatus comprising two customer lead in units each as  
35 defined above, one unit being positioned at the mouth of the aperture at the external surface of the wall, the other being positioned at the mouth of the aperture at the internal

- 4 -

surface of the wall.

The invention will now be described in greater detail, by way of example, with reference to the accompanying drawings, in which: -

5        Figure 1 is a exploded perspective view of a wall plug and a bend control piece of a CLI unit constructed in accordance with the invention;

Figure 2 is a plan view of the CLI unit of Figure 1; and

10       Figure 3 is a cross-section taken through the cavity wall of a telecommunications network customer, and shows two CLI units of the type shown in Figures 1 and 2 in place to guide optical fibre into that customer's premise.

Referring to the drawings, Figures 1 and 2 show a CLI  
15       unit C constituted by an externally-fluted wall plug 1 and a pair of complementary bend control pieces 2. In use, the bend control pieces 2 fit together with complementary surfaces 2a thereof in engagement. The wall plug 1 and the two bend control pieces 2 are each moulded from an ultra  
20       violet (uv) stable plastics material such as polypropylene. One end of the wall plug 1 is formed with an annular flange 1a, this flange being a mating fit within complementary recesses 3 formed in the surfaces 2a of the bend control pieces 2. The wall plug 1 is formed with an axial bore 1b  
25       through which, in use, a tube containing optical fibre can pass. When the CLI unit C is assembled (with the flange 1a of the wall plug 1 positioned within the recesses 3 of the bend control pieces 2, and with the surfaces 2a in face-to-face engagement), the mouth of the bore 1b leads to a curved  
30       channel defined by a pair of complementary grooves 4 formed in the surfaces 2a. When in the assembled position, the CLI unit C can be fixed to the wall of a customer's premises by means of screws (not shown) passing through aligned apertures  
35       5 pre-formed in the bend control pieces 2. The screws also act to fix the two bend control pieces 2 together around the flange 1a of the wall plug 1. When fixed to the wall, the engagement of the flange 1a within the recesses 3 holds the



- 5 -

wall plug 1 firmly with respect to the bend control pieces 2.

The grooves 4 are such as to curve through  $90^\circ$  with a radius of curvature which is 30mm (that is to say the minimum bend radius for the standard signal mode optical fibre normally used for telecommunications). The grooves 4 have a diameter of 5.2mm so as to accommodate the tubing 6 (see Figure 3) through which blown fibre is installed. The CLI unit C thus constitutes a simple device for guiding optical fibre through  $90^\circ$  without subjecting that fibre to bends which would cause a significant optical loss.

Figure 3 shows two CLI units C positioned on opposite sides of an external cavity wall of a customer's premises, the wall plugs 1 of the units frictionally fitting within 13mm bores 7 drilled in the inner and outer cavity wall portions 8a and 8b respectively. As shown in Figure 3, the blown fibre tubing 6 passes along the inside surface of the inner cavity wall portion 8a, through each of the CLI units C, and then along the outside surface of the outer cavity wall portion 8b. The tubing 6 can be fixed to the wall portions 8a and 8b by any suitable means.

- 6 -

CLAIMS

1. A customer lead in unit for guiding an optical fibre transmission line through an aperture in the wall of a customer's premises, the unit comprising a hollow wall plug  
5 which is frictionally engageable within said aperture, and a pair of complementary bend control pieces, each bend control piece having a bend control surface formed with a curved bend control groove whose curvature conforms with minimum bend  
10 the bend control pieces being formed with engagement portions which inter-engage with a complementary engagement portion formed at one end of the wall plug to grip the wall plug between the two bend control pieces, and the bend control  
15 grooves being positioned so as to define a bend control channel that is contiguous with the hollow interior of the wall plug when the wall plug is gripped by the two bend control pieces.
2. A customer lead in unit as claimed in claim 1, wherein a flange formed at said one end of the wall plug constitutes  
20 the complementary engagement portion, and each of the bend control pieces is formed with a complementary groove formed in its bend control surface, said grooves constituting the engagement portions.
3. Customer lead in apparatus for guiding an optical  
25 fibre transmission line through an aperture in the wall of a customer's premises, the apparatus comprising two customer lead in units each as claimed in claim 1 or claim 2, one unit being positioned at the mouth of the aperture at the external surface of the wall, the other being positioned at the mouth  
30 of the aperture at the internal surface of the wall.

1/2




Fig.1





Fig.2

2/2

Fig.3.



# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/GB 95/00449

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 G02B6/00 G02B6/44

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 G02B H02G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE,A,39 11 095 (LANCIER) 11 October 1990 see claims; figures	1-3
A	REVIEW ELECTRICAL COMMUNICATION LABORATORIES, vol.32, no.4, 1984, JP pages 636 - 645 S.KUKITA 'design and performance of optical drop and indoor cable'	1-3
A	US,A,4 596 381 (J.C.HAMRICK) 24 June 1986 see claims; figures	1-3
A	DE,U,91 14 452 (OTTO) 19 March 1992 see claims; figures	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*I\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

26 May 1995

Date of mailing of the international search report

- 9. 06. 95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+ 31-70) 340-3016

Authorized officer

Pfahler, R

# INTERNATIONAL SEARCH REPORT

information on patent family members

Int: International Application No

PCT/GB 95/00449

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-A-3911095	11-10-90	NONE	
US-A-4596381	24-06-86	CA-A- 1156211	01-11-83
DE-U-9114452	19-03-92	NONE	

1/2




Fig.1





Fig.2

Fig.3.



**SUBSTITUTE SHEET**



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)